

10/618,095

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Kristofer J. James et al.

Examiner: Tibbits, Pia

Patent No.: 7,239,146

Group Art Unit: 2838

. Issue Date: July 3, 2007

Docket No: 279.645US1

Title: INDICATOR OF REMAINING ENERGY IN STORAGE CELL OF IMPLANTABLE MEDICAL

DEVICE

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

ATTN: CERTIFICATE OF CORRECTION BRANCH

DEC 1 9 2007

of Correction

We are transmitting herewith the attached:

Request for Certificate of Correction.

Certificate of Correction Form - PTO-1050 (in duplicate)

A return postcard.

Please charge any additional fees or credit overpayment to Deposit Account No. 19-0743.

SCHWEGMAN, LUNDBERG & WOESSNER, P.A.

Customer No: 21186

Name: Suneel Arora

Reg. No.42,267 SA:CMG:raq

CERTIFICATE UNDER 37 CFR 1.8: The undersigned hereby certifies that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail, in an envelope addressed to: Commissioner of Patents and Trademarks, P.O. Box 1450, Alexandria VA 22313-1450, on this _____ day of December 2007.

alysha Knamber

Patent 7,239,146

PATENT PATENT AND TRADEMARK OFFICE

7,239,146 Patent No.:

Docket No:

279.645US1

Issue Date:

July 3, 2007

Patentee: Kristofer J. James et al.

Customer No.: 21186

Confirmation No.: 3840

Title

INDICATOR OF REMAINING ENERGY IN STORAGE CELL OF

IMPLANTABLE MEDICAL DEVICE

REQUEST FOR CERTIFICATE OF CORRECTION

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

ATTN: CERTIFICATE OF CORRECTION BRANCH

DEC 1 7 2007

It is requested that a Certificate of Correction be issued correcting printing errors appearing in the above-identified United States patent. Two copies of the text of the Certificate in the suggested form are enclosed.

Issuance of the Certificate of Correction would neither expand nor contract the scope of the claims as properly allowed, and re-examination is not required.

As the error is that of the Patent Office, it is believed that no fee is due.

The Examiner is authorized to charge any additional fees or credit overpayment to Deposit Account No.19-0743.

Respectfully Submitted,

SCHWEGMAN, LUNDBERG & WOESSNER, P.A.

P.O. Box 2938

Minneapolis, MN 55402

(612) 373-6900

Date: Dec. 11, 2007

Suneel Árora

Reg. No: 42,267

SA:raq

CERTIFICATE UNDER 37 CFR § 1.8: The undersigned hereby certifies that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail, in an envelope addressed to: Commissioner for Patents, P.O. Box 1450 Alexandria, VA 22313-1450, on this day of December 2007

Isha Mamber

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO

: 7,239,146

Page (1) of 2

DATED

: July 3, 2007

INVENTOR(S)

: James et al.

It is certified that errors appear in the above-identified patent and that said Letters Patent

is hereby corrected as shown below:

In column 11, line 13, below "the cell."

insert - - 18. A system comprising:

an energy storage cell;

a current source/sink circuit, coupled to the cell, to draw a substantially constant first current pulse; a voltage measurement circuit, coupled to the cell, to measure first and second voltages during the first current pulse;

means for measuring a first change of a terminal voltage across the cell during the first time period, in which the measuring the first change of the terminal voltage comprises measuring a polarization

a difference circuit, coupled to the voltage measurement circuit, to compute a difference between the first and second voltages; and

a processor circuit, coupled to or including the difference circuit, the processor circuit including a memory circuit to store first data relating cell capacity to the difference between the first and second voltages, the memory circuit also including a cell capacity indicator storage location to provide an indication of cell capacity, the processor configured to use the difference between the first and second voltages obtained from the difference circuit and the polarization angle and the stored first data indicative of cell capacity to provide the indication of cell capacity.

- 19. The system of claim 18, in which the energy storage cell comprises a manganese dioxide battery cell.
- The system of claim 18, in which the energy storage cell comprises a silver vanadium oxide cell.
- 21. The system of claim 18, in which the voltage measurement circuit is also configured to measure a quiescent voltage.
- 22. The system of claim 21, in which the processor is configured to compare the measured quiescent voltage to a predetermined threshold to distinguish between two different stored cell capacity values that correspond to a single difference in terminal voltage across the cell.

MAILING ADDRESS OF SENDER:	PATENT NO7,239,146
SCHWEGMAN, LUNDBERG & WOESSNER, P.A.	No. of additional copie
P.O. BOX 2938	<u> </u>
Minneapolis, MN 55402	<u>└</u> -,

Atty Docket No: 279.645US1

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO

: 7,239,146

Page (2) of 2

DATED

: July 3, 2007

INVENTOR(S)

: James et al.

It is certified that errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

- 23. The system of claim 21, in which the memory circuit is also configured to store second data relating cell capacity to the quiescent voltage, and in which the processor is configured to compare the measured quiescent voltage to the second data to determine the energy remaining in the cell.
- 24. The system of claim 23, in which the processor is configured to determine the energy remaining in the cell using the difference, during an earlier portion of a life of the cell, and using the measured quiescent voltage, during the later portion of a life of the cell.
- 25. The system of claim 18, in which the processor is configured to compare first and second differences to distinguish between two different stored first data values that correspond to a single stored difference.
- 26. The system of claim 18, in which the processor is located within an implantable medical device.
- 27. The system of claim 18, in which the processor is located within an external remote interface device.

In column 12, line 1, in claim 18, delete "18." and insert - - 28. - -, therefor.

MAILING ADDRESS OF S	EMILED

PATENT NO. _____ 7,239,146

SCHWEGMAN, LUNDBERG & WOESSNER, P.A. P.O. BOX 2938
Minneapolis, MN 55402

No. of additional copies

Atty Docket No: 279.645US1

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number. (Also Form PTO-1050)

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO

: 7,239,146

Page (1) of 2

DATED

: July 3, 2007

INVENTOR(S)

: James et al.

It is certified that errors appear in the above-identified patent and that said Letters Patent

is hereby corrected as shown below:

In column 11, line 13, below "the cell."

insert - - 18. A system comprising:

an energy storage cell;

Atty Docket No: 279.645US1

a current source/sink circuit, coupled to the cell, to draw a substantially constant first current pulse; a voltage measurement circuit, coupled to the cell, to measure first and second voltages during the first current pulse;

means for measuring a first change of a terminal voltage across the cell during the first time period, in which the measuring the first change of the terminal voltage comprises measuring a polarization angle;

a difference circuit, coupled to the voltage measurement circuit, to compute a difference between the first and second voltages; and

a processor circuit, coupled to or including the difference circuit, the processor circuit including a memory circuit to store first data relating cell capacity to the difference between the first and second voltages, the memory circuit also including a cell capacity indicator storage location to provide an indication of cell capacity, the processor configured to use the difference between the first and second voltages obtained from the difference circuit and the polarization angle and the stored first data indicative of cell capacity to provide the indication of cell capacity.

- 19. The system of claim 18, in which the energy storage cell comprises a manganese dioxide battery cell.
- 20. The system of claim 18, in which the energy storage cell comprises a silver vanadium oxide cell.
- 21. The system of claim 18, in which the voltage measurement circuit is also configured to measure a quiescent voltage.
- 22. The system of claim 21, in which the processor is configured to compare the measured quiescent voltage to a predetermined threshold to distinguish between two different stored cell capacity values that correspond to a single difference in terminal voltage across the cell.

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO

: 7,239,146

Page (2) of 2

DATED

: July 3, 2007

INVENTOR(S)

: James et al.

It is certified that errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

- 23. The system of claim 21, in which the memory circuit is also configured to store second data relating cell capacity to the quiescent voltage, and in which the processor is configured to compare the measured quiescent voltage to the second data to determine the energy remaining in the cell.
- 24. The system of claim 23, in which the processor is configured to determine the energy remaining in the cell using the difference, during an earlier portion of a life of the cell, and using the measured quiescent voltage, during the later portion of a life of the cell.
- 25. The system of claim 18, in which the processor is configured to compare first and second differences to distinguish between two different stored first data values that correspond to a single stored difference.
- 26. The system of claim 18, in which the processor is located within an implantable medical device.
- 27. The system of claim 18, in which the processor is located within an external remote interface device.

In column 12, line 1, in claim 18, delete "18." and insert - - 28. - -, therefor.

N 4 A	tt	DIC	ADD	RESS	OF	CEN	DED.
MA	1L	D/II.	AUU	KE33	Ur	SEIN	DEK.

PATENT NO. ___

_7,239,146__

No. of additional copies

[_

Atty Docket No: 279.645US1

SCHWEGMAN, LUNDBERG & WOESSNER, P.A. P.O. BOX 2938

Minneapolis, MN 55402

➡ ___